

SPOTTING FLUID FOR DIFFERENTIAL STICKING

Inventors:

**James D. Kercheville
Houston, Texas**

**Kenneth W. Pober
Houston, Texas**

SPOTTING FLUID FOR DIFFERENTIAL STICKING

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to compositions and methods for unsticking or freeing differential stuck pipe used in drilling a borehole for hydrocarbons in a subterranean formation.

2. Description of Relevant Art

Rotary drilling methods employing a drill bit and drill stems have long been used to drill wellbores in subterranean formation. Drilling fluids or muds are commonly circulated in the well during such drilling to cool and lubricate the drilling apparatus, lift cuttings out of the wellbore, and counterbalance the subterranean formation pressure encountered. The specific gravity of a well fluid is normally adjusted in such a way that the pressure of the fluid on the rock formations exceeds the formation pressure on the well. As a result, liquid components of the well fluid are forced into the formation surrounding the well while insoluble components settle on the walls of the well in the form of a stabilizing "filter cake."

Inevitably in drilling a well, the path followed by the drill pipes will deviate some from the vertical or other desired path for the well. At such consequent deviations or "kinks," the rotating drill pipes may come into contact with the filter cake and even with the wall of the well and become buried therein, resulting in jamming or sticking.

Such jamming or sticking is particularly common when pipe connections, which are larger in diameter than the drill pipes themselves, come into contact with the kinks.

The most frequent cause of jamming or sticking of drill pipes is differential jamming. Differential jamming can occur when the rotation of the drill pipes is stopped. If a drill pipe then comes into contact with the filter cake adhering to the wall of the well, the drill pipe is forced into the wall of the well by the hydrostatic pressure of the column of mud. The contact surface is then isolated from the mud pressure. If, as is usually the case, the mud pressure is greater than the formation pressure, the contact surface is held fast to the wall by suction forces. The suction force increases with the thickness and compressibility of the filter cake. With time, even relatively large sections of the drill pipe can become held fast. Thus, prompt treatment is best.

1 Prompt freeing of the stuck drill pipe is also needed to alleviate lost drilling time and the consequent costs which that involves.

 Spotting fluids are used by those skilled in the art to free stuck drill pipe. Spotting fluids need a good lubricating effect and the ability to ensure good oil wettability of the surfaces of the drill pipe and of the walls of wells coming into contact with the drill pipe.

6 To maximize utility in freeing stuck pipe, the spotting fluid should be applied at exactly the point in the well at which the pipe has become stuck. This is accomplished in the same general way in which the well fluid is introduced into the well. Instead of the well fluid, the spotting fluid is forced through the interior of the drill pipe to the bit, which leaves the bit, and slowly ascends in the well to the point of the stuck pipe. Thus, it is critically important to be able to exactly adjust the
11 specific gravity of the spotting fluid so that it will be such as to keep the spotting fluid at that location in the well of the stuck pipe for sufficient time for its lubricity-enhancing properties to act to free the stuck pipe.

 Since prompt use of a spotting fluid is important, it is standard practice at the drill site to store spotting fluid or spotting fluid concentrates which may rapidly be adjusted to the required
16 density and consistency by addition of barite or other weighting materials and optionally other additives and water.

 Spotting fluids known in the art typically consist of hydrocarbon mixtures, often based on diesel oils or mineral oils. Emulsifiers and surfactants are typical additives.

 Such prior art spotting fluids may cause environmental concerns if they come into contact
21 with ground soil formations. Further, since oil based spotting fluids mix with the drilling fluid during discharge from the well, such oil based spotting fluids contaminate the water based drilling fluids which then have to be discarded and separately treated to avoid environmental concerns., adding further to the drilling costs. The environmental concerns are enhanced in off-shore drilling where there is less space to store discarded fluids for treatment.

26 U.S. Patent No. 4,964,614 issued in 1990 to Mueller et al. discloses an ester based spotting fluid that is said to have fewer environmental concerns than the mineral oil or diesel oil based fluids. However, a need continues to exist for more efficient and improved, environmentally friendly spotting fluids that are effective in freeing stuck pipe.

SUMMARY OF THE INVENTION

The composition and method of the present invention are useful in treating and alleviating stuck pipe, particularly differential stuck pipe, during drilling of a wellbore in a subterranean formation. The preferred composition of the invention is an invert oil mud system comprising iso-butyl oleate as the external phase and glycerin (preferably) or calcium chloride (CaCl_2) solution as the internal phase. For application to stuck pipe downhole, this emulsion may be combined with, added to, or mixed with other fluids for carrying the emulsion to the treatment site and holding it there long enough to free the stuck pipe.

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a new composition and method of using such composition for freeing stuck drill pipes. The composition and method are particularly useful in freeing differential stuck pipe.

The composition of the invention comprises a water-in-oil emulsion or an invert oil mud system. The emulsion comprises iso-butyl oleate as the external phase and either glycerin (preferably) or calcium chloride as the internal phase, preferably in a ratio ranging from about 95:5 to about 50:50 oil phase to water phase or more specifically oleate to either glycerin or about 38% aqueous calcium chloride solution. This emulsion may be added to or mixed with other treatment products and with materials or products to facilitate delivery of the emulsion to the site of the stuck pipe and holding of the emulsion at such site sufficient time to enable the emulsion to cause or effect unsticking of the pipe. Such typical additives or additional materials include, for example, about 2 to about 14 pounds per barrel EZ-MUL NTE™ (an emulsifier/oil wetting agent), available from Halliburton Energy Services, Inc., Houston, Texas; about 0.5 to about 3.0 pounds per barrel DRILTREAT™ (a supplemental oil wetting agent), available from Halliburton Energy Services, Inc., Houston, Texas; about 2 to about 6 pounds per barrel GELTONE II™ (a viscosifier or suspending agent), available from Halliburton Energy Services, Inc., Houston, Texas; and barite as needed for desired fluid density.

An example formulation of a preferred spotting fluid of the invention comprises, as the external phase, about 0.7 barrel (bbl) of iso-butyl oleate as the external phase and, as the internal

1 phase, about 0.3 bbl of glycerin. This formulation is combined with about 8 lb/bbl of EZ-MUL
NTET[™]; about 1 lb/bbl of DRILTREAT[™]; about 3 lb/bbl of GELTONE II; and barite as needed for
desired density.

6 The iso-butyl oleate/glycerin invert emulsion of the invention has the advantageous ability
to not only lubricate the surfaces involved in sticking of the metal (of drill pipe or other stuck
equipment in the filter cake) but also to dehydrate or destruct the filter cake for enhanced
performance as a spotting fluid. The iso-butyl oleate oil phase is effective at lubricating the surfaces
and penetrating the filter cake. Glycerin is effective at dehydrating the filter cake. In fact, glycerin,
with an $a_w \approx 0.0$ (a_w means activity, water phase), is even better at such dehydration than is calcium
chloride, with an $a_w \approx 0.30$, which has been known to be effective at dehydrating filter cakes.

11 The emulsions of the invention were tested for performance as a spotting fluid in a
differential sticking tester, or STICKOMETER[™], manufactured by and available from Halliburton
in Houston, Texas. The STICKOMETER[™] consists of a modified filtration cell in which a mud
cake to be tested is deposited by filtration of a mud under pressure. A flat plate is pressed under load
onto the mud cake. Spotting fluid is then allowed to soak around the mud cake and stuck plate
16 apparatus. After a period of time, typically about 16 hours, torque-to-free is measured. This torque
is a relative measure of sticking tendency. A typical test procedure follows. Already prepared mud
was allowed to filter under 500 psi pressure, generating a mud cake, while collecting 10 ml of
filtrate. The metal disk was then stuck in the mud cake, and 2 ml of additional filtrate was collected.
For base mud, filtering was done overnight without collecting the 2 ml of filtrate. For spotting fluid
21 evaluation, the pressure was relieved after 2 ml of filtrate, the base mud decanted, then spotting fluid
loaded into the cell. Pressure was reapplied and filtration continued overnight, for about 16 hours.
The torque was measured the next morning while maintaining 500 psi pressure on the cell.

26 In testing this invention, an invert-oil emulsion of iso-butyl oleate and glycerine was
prepared and tested in a STICKOMETER[™] and test results --torque to free in inch pounds (in/lbs)--
and compared to results with other fluids, including known spotting fluids and commercially
available spotting fluids such as COASTAL SPOT[™], available from Coastal Mud and Coastal Fluid
Technologies, Lafayette, Louisiana, a division of Coastal Chemical Co., LLC a Holland Chemical
International Co. Tables 1. through 4 show the performance of various experimental and

commercial spotting fluid treatments in selected mud systems. In each case, the isobutyl oleate/glycerine composition of the present invention yielded equal or better results than any product tested.

TABLE 1

6

11

16

21

26

<u>Mud System/Spot</u>	<u>Torque-to-Free (in/lbs)</u>
Base A (16 ppg Freshwater Lignosulfonate)	350
Base A with addition of:	
Diesel oil	170
11.6 CaCl ₂ brine	110
12.7 NaBr brine	190
12.7 NaBr brine/3% TORQ TRIM II™	150
12.7 NaBr brine/3% FSE Fluoro-surfactant	150
30% 12.7 NaBr brine/70% Glycerine	200
Squalane C ₃₀ H ₆₂	120
Squalene C ₃₀ H ₅₀	180
Isobutyl Oleate Neat	60
Oleyl Oleate Neat	80
16 ppg COASTAL SPOT™/CaCl ₂	50
16 ppg COASTAL SPOT™/NaCl	170
16 ppg Phase 1 of DUAL PHASE™	110
16 ppg Phase 1 & 2 of DUAL PHASE™	110
16 ppg Isobutyl Oleate/CaCl ₂	70
16 ppg Isobutyl Oleate/Glycerine	40
16 ppg Oleyl Oleate/Glycerine	55

1 TORQ TRIM II™ is available from Halliburton Energy Services, Inc. in Houston, Texas;
 COASTAL SPOT™ is available from Coastal Mud and Coastal Fluid Technologies in Lafayette,
 Louisiana; and DUAL PHASE™ is available from Halliburton Energy Services, Inc. in Houston,
 Texas.

6 The base mud in Table 1 is a 16 lb/gal freshwater/lignosulfonate mud. This base mud shows
 torque-to-free at 350 inch-pounds, a “high” number in terms of sticking tendency, indicating the mud
 alone likely will not be able to free a stuck pipe. A low torque-to-free number represents or indicates
 low sticking tendency. As shown in Table 1, all of the various spotting fluid treatments provided
 some improvement over the base mud for purposes of freeing stuck pipe. The isobutyl
 oleate/glycerine system of the present invention yielded the best performance, with a very low
 11 torque-to-free number of 40.

TABLE 2

	<u>Mud System/Spot</u>	<u>Torque-to-Free (in/lbs)</u>
16	Base B (16 ppg Seawater Lignosulfonate)	280
	Base B with addition of:	
	16 ppg COASTAL SPOT™/CaCl ₂	300
	16 ppg ENVIRO-SPOT™/Freshwater	270
	16 ppg Phase 1 of DUAL PHASE™	290
21	16 ppg Phase 1 & 2 of DUAL PHASE™	290
	16 ppg Isobutyl Oleate/Glycerine	210
	16 ppg Isobutyl Oleate/Glycerine (after 250°F hot roll)	180

26 COASTAL SPOT™ is available from Coastal Mud and Coastal Fluid Technologies in Lafayette,
 Louisiana; ENVIRO-SPOT™ is available from Halliburton Energy Services, Inc. in Houston, Texas;
 and DUAL PHASE™ is available from Halliburton Energy Services, Inc. in Houston, Texas.

Table 2 shows results with a 16 lb/gal seawater/lignosulfonate mud system. The control or

base mud has a torque-to-free value of 280 in/lbs. Best performance again was with the isobutyl oleate/glycerine composition of the present invention, providing a torque-to-free of 210 in/lbs. Hot rolling this spotting fluid at 250°F before conducting the STICKOMETER™ test yielded further improved results.

TABLE 3

<u>Mud System/Spot</u>	<u>Torque-to-Free (in/lbs)</u>
Base C (16 ppg POLYNOX™)	380
Base C with addition of:	
16 ppg COASTAL SPOT™/CaCl ₂	240
16 ppg Phase 1 of DUAL PHASE™	260
16 ppg Isobutyl Oleate/Glycerine	160
Base D (16 ppg PHPA Mud)	205
Base D with addition of:	
16 ppg COASTAL SPOT™/CaCl ₂	160
16 ppg Phase 1 of DUAL PHASE™	155
16 ppg Isobutyl Oleate/Glycerine	170

POLYNOX™ is available from Halliburton Energy Services, Inc. in Houston, Texas; COASTAL SPOT™ is available from Coastal Mud and Coastal Fluid Technologies in Lafayette, Louisiana; and DUAL PHASE™ is available from Halliburton Energy Services, Inc. in Houston, Texas.

Table 3 shows some limited results with a POLYNOX™ mud and with a PHPA (partially-hydrolyzed, polyacrylamide) based mud, both at 16 lb/gal. Again, isobutyl oleate/glycerine of the present invention showed the best results in the POLYNOX™ system. COASTAL SPOT™, DUAL PHASE™ and isobutyl oleate/glycerine of the present invention showed about the same performance in the PHPA mud system.

TABLE 4

<u>Mud System/Spot</u>	<u>Torque-to-Free (in/lbs)</u>
Base E (12 ppg Freshwater Lignosulfonate)	185
Base E with addition of:	
12 ppg DUAL PHASE™	115
12 ppg COASTAL SPOT™-old	75
12 ppg COASTAL SPOT™-new	70
12 ppg Isobutyl Oleate/Glycerine	80

Table 4 shows results with a 12 lb/gal freshwater/lignosulfonate mud system. Three commercial products and the isobutyl oleate/glycerine composition of the present invention showed similar performance in this mud system. With each, torque was reduced by over 50%.

Further, the iso-butyl oleate/glycerin composition of the present invention is environmentally acceptable. Mysid shrimp LC₅₀ tests were conducted according to industry standards. An invert emulsion comprising the oleate/glycerin composition was evaluated at 5 and 10 volume % in generic # 7 drilling fluid (industry standard). Results for 96-hour LC50 in mg/L SPP were 267,600 and 227,700 respectively. Gulf of Mexico minimum by regulation is 30,000. Operators prefer 100,000 or more.

Without wishing to limit the invention, it is expected that the isobutyl oleate/glycerine composition of the present invention would be used over a density range of about 10 to about 16 lb/gal., depending on the circumstances of the case, and likely particularly associated with the well and the stuck pipe. Table 5 shows rheology and mud properties for an isobutyl oleate/glycerine invert mud system at 10, 13 and 16 lb/gal densities. These values in Table 5 are consistent with a reliable and stable mud system over this density range.

1 The single asterisk in Table 5 designates values for the experimental spotting fluid which
comprised 8 lb EZ MUL NTE™ and 1 lb DRIL TREAT™ in a barrel of isobutyl oleate. Double
asterisks in Table 5 designates values for Experimental Spotting Fluid (Sample G) which comprised
8 lb EZ MUL NTE™ and 1 lb DRIL TREAT™ in a barrel of oleyl oleate. Triple asterisks in Table
5 designates values for Sample H which comprised COASTAL SPOT™ which comprised a 16.0
6 *lb/gal pill mixed according to COASTAL SPOT™ guidelines.*

 Table 6 shows a decided advantage of the invention. The test results of Table 6 show not
only the effectiveness of the oleate/glycerin invert emulsion as a spotting fluid, but also that such
spotting fluid in the water-based drilling fluid does not have to be separated and removed from the
operating mud system after use, saving time and money. Spotting fluid volumes are typically about
11 50 to about 100 barrel "pills" in operating mud systems of about 1000 barrels or more. Once stuck
pipe is no longer stuck, i.e., is free, the spotting fluid composition of the present invention used to
free the pipe can be circulated in with the operating mud system. Table 6 shows that up to about 10
volume percent of isobutyl oleate/glycerine fluid mixed in with a seawater/lignosulfonate mud
creates no final mud problems. To the contrary, the lubricity of the final mud mixture is improved
16 some by leaving in the isobutyl oleate/glycerine, a further advantage of the invention.

TABLE 6
CONTAMINATION TESTS (sea water mud)
Initial Properties and Properties After Hot Rolling at 150°F and 250°F

Sample Mark	A	A	B	B	C	C	AA	D	D	DD
Base Mud*, bbl	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Experimental Spotting Fluid Pill, bbl	---	---	0.05	0.05	0.10	0.10	---	0.10	0.10	0.10
Q-BROXIN™, lb	---	---	---	---	---	---	---	2.0	2.0	2.0
CARBONOX™, lb	---	---	---	---	---	---	---	2.0	0.0	1.0
Caustic soda, lb								1.0	1.0	1.0
Stirred, min	15	15	15	15	15	15	15	15	15	15
Rolled at 150°F, hr	0	16	0	16	0	16	16	0	16	16
Rolled at 250°F, hr	---	---	---	---	---	---	16	---	---	16
Test Temp., °F	80	80	80	80	80	80	80	80	80	80
Mud Density, lb/gal.	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0
Plastic Viscosity, cp	40	44	34	38	39	38	37	35	41	39
Yield Point, lb/100 sq. ft	18	13	36	31	41	36	13	25	19	13
10 sec gel, lb/100 sq ft	7	6	16	12	20	17	4	8	7	5
10 min gel, lb/100 sq ft	21	18	40	30	50	41	12	24	18	15
pH	9.7	9.4	9.8	9.5	9.7	9.2	8.9	11.7	11.2	9.2
API Filtrate, ml	---	2.6	---	3.2	---	3.6	---	---	3.0	---
Filtrate, 250°F, 500 psi, ml	---	8.4	---	10.0	---	9.8	---	---	8.2	---
FANN 35: 600 rpm	98	101	104	107	119	112	87	95	101	91
300 rpm	58	57	70	69	80	74	50	60	60	52
200 rpm	45	43	55	57	65	63	38	50	48	44
100 rpm	30	27	37	38	48	45	21	30	28	22
6 rpm	9	7	18	14	24	19	5	9	8	6
3 rpm	7	6	16	12	22	17	4	8	7	5
LUBRICITY COEFFICIENT	---	0.23	---	---	---	---	---	---	0.18	---
% Lubricity Improvement	---	---	---	---	---	---	---	---	21.7	---

1 The Base Mud in Table 6 is comprised of 0.72 bbl sea water, 12 lb AQUAGEL™, 30 lb Rev Dust, 4 lb Q-BROXIN™, 1 lb caustic soda, 416 lb barite and 0.5 lb BARAZAN PLUS™. AQUAGEL™ is available from Halliburton Energy Services, Inc. in Houston, Texas; Q-BROXIN™ is available from Halliburton Energy Services, Inc. in Houston, Texas; and BARAZAN PLUS™ is available from Halliburton Energy Services, Inc. in Houston, Texas.

6 In the method of the invention, a spotting fluid comprising an invert water-in-oil emulsion of the invention--glycerin or calcium chloride brine in isobutyl oleate--is used to free stuck pipe, particularly differentially stuck pipe.

 The foregoing description of the invention is intended to be a description of preferred embodiments. Various changes in the details of the described composition and method can be made
11 without departing from the intended scope of this inventions as defined by the appended claims.